



**NATIONAL DISTRIBUTOR OF QUALITY
MAINTENANCE SUPPLIES SINCE 1958**

1-800-558-2808



MY ACCOUNT SERVICES PDF CATALOG CHARTS MSDS NEW PRODUCTS ABOUT US CONTACT US HELP

Home > Products > Chemicals & Paint > MSDS Sheets > MSDS 7676 -- [Back]

LOGIN

Login E-mail: _____

Password: _____



Apply for an account! »

PRODUCT SEARCH

Advanced Search »

- All Products
- Fasteners
 - » Grade 8
 - » Grade 5
 - » Threaded Fasteners
- Hardware
- Rivet & Rivet Guns
- Vehicle Lighting
- Electrical Products
- Tubing & Tube Fittings
- Air Brake Products
- Hose & Hose Ends
- Cutting Tools
- Abrasives
- Safety Products & Welding Supplies
- Chemicals & Paint
 - » MSDS Information
 - » CA/OTC Information
- Shop Supplies
- Vehicle Parts & Accessories
- Assortments & Steel Equipment
 - » Assortment Listing

- Online Catalog Index
- Discontinued & Overstock Specials

Printer-Friendly View

MSDS 7676

7676: Lubriplate Chain & Cable Spray [12]
MSDS Last updated: 05/14/2008

LUBRIPLATE MATERIAL SAFETY DATA SHEET Section 1

PRODUCT NAME OR NUMBER:
LUBRIPLATE Chain & Cable Fluid (Aerosol) (New Formula)

FORMULA:
Mineral Oil, Additives and Propellant

GENERIC/CHEMICAL NAME:
Petroleum Lubricating Oil

NSF Registration No:
N/A

Manufacturer's Name:
Fiske Brothers Refining Co.,
d/b/a LUBRIPLATE Lubricants Co.

Emergency Telephone Number:
1-800-255-3924 CHEM-TEL (24 hour)

Address:
1500 Oakdale Ave., Toledo, OH 43605
129 Lockwood St., Newark, NJ 07105

Telephone Number for Information:
419-691-2491 - Toledo Office

Section 2 - Composition/Information on Ingredients

Ingredients with CAS #'s	CAS #	Percentage
Mineral Oil	64742-52-5	45 - 50%
Mineral Oil	64742-53-6	20 - 25%
LPG (Propellant)	68476-86-8	20%
Corrosion Inhibitor	N/A - Mixture	0 - 2%
2-Butoxyethanol	111-76-2	0 - 3%

Hazardous Material Identification System (HMIS):
Health - 1, Flammability - 4, Reactivity - 0

WHMIS Hazard Class (Canada): D/1/A
Special Protection: See Section 9

Section 3 - Health Hazard Data

Threshold Limit Value: TLV for oil mist = 5mg/m3

Effects of Overexposure: Inhalation is the most likely method of exposure. Minimal effects are expected at levels below the TLV of components. Dizziness, drowsiness, coughing, nasal or throat irritations at higher levels. Propellant may cause myocardial irritation and may act as a simple asphyxiant without other significant physiologic effects if the oxygen content is low.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Section 4 - Emergency and First Aid Procedures

EYE CONTACT: Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

SKIN CONTACT: Remove any contaminated clothing and wash exposed area with soap and warm water.

INHALATION: Remove to fresh air. If breathing has stopped, administer artificial respiration. Get medical help immediately.

INGESTION: If ingested, call a physician immediately. Do not induce vomiting.

Section 5 - Fire and Explosion Hazard Data

Flash Point (Method Used): Propellant < 0°F
 Flammable Limits: LEL 0.9% UEL 9.5%

Extinguishing Media: Foam, Dry Chemical, Carbon Dioxide.

Special Fire Fighting Procedures: Keep containers cool. Use air-supplied breathing equipment for enclosed or confined spaces. Use shielding to protect personnel against bursting containers.

Unusual Fire and Explosion Hazards: Do not spray near open flame. At elevated temperatures (over 130°F.), aerosol containers may vent, burst, or rupture.

Section 6 - Physical/Chemical Characteristics

Boiling Point: (Aerosol) N/A Specific Gravity (H 20 = 1) 0.93
 of Product:

Vapor Pressure (mm Hg.): Aerosol @ 130°F. - 80 psig Melting Point: Spray

Vapor Density (AIR = 1): >1 Evaporation Rate: Faster
 (Butyl Acetate = 1)

Solubility in Water: Insoluble

Appearance and Odor: Off-white mist with additive odor from aerosol can.

Section 7 - Reactivity Data

Stability: Unstable Conditions to Avoid:
 Stable X Avoid spraying into open flame or onto red-hot surfaces.

Incompatibility (Materials to Avoid): Strong oxidizers.

Hazardous Decomposition or Byproducts: May form Carbon Monoxide, Hydrogen Chloride.

Hazardous Polymerization: May Occur Conditions to Avoid: N/A
 Will Not Occur X

Section 8 - Spill or Leak Procedures

Steps to be taken in case material is released or spilled:
 Remove sources of ignition, ventilate area. Use appropriate safety equipment to enter area. Allow time for vapors to be below their TLV.
 Add oil absorbent and clean area. Keep petroleum products out of sewers and watercourses.

Waste disposal method:

Do not puncture or incinerate containers. Give empty, leaking or full containers to a disposal service equipped to safely handle and dispose of pressurized containers.

SARA/Title III, Section 313 Status Ethylene Glycol Monobutyl Ether (Glycol Ether Category) <3%.

Section 9 - Special Protection Information

Respiratory Protection (Specify type): Need approved organic vapor mask if TLV is exceeded.

Ventilation: Local Exhaust Use for fumes & to maintain below TLV value.
 Mechanical (General) Special: N/A
 Other: N/A

Protective Gloves: Use oil-impervious gloves, such as nitrile.

Eye Protection: Use goggles or face shield.

Other Protective Equipment: Use oil-resistant apron, if needed.

Section 10 - Special Precautions

Precautions to be taken in handling and storing:
Store in cool, dry area out of direct sunlight. Do not puncture or incinerate, or heat full or empty containers above 130°F.

Other Precautions:
Please read and follow the directions on the product label. Keep away from children.

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Fiske Brothers Refining Co., d/b/a LUBRIPLATE Lubricants Co. The data on these sheets relates only to the specific material designated herein. Fiske Brothers Refining Co., d/b/a LUBRIPLATE Lubricants Co. assumes no legal responsibility for use or reliance upon this data.

Date Prepared: September 19, 2007
Prepared by: James R. Kontak

The information contained in this MSDS was obtained from current and reliable sources, however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of Imperial Supplies LLC, Imperial will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.

For more product information by email, [click here](#)

Imperial Supplies LLC does not provide services and products outside the United States

[Home](#) | [My Account](#) | [Print Catalog](#) | [On-line Catalog](#) | [New Products](#) | [Imperial Services](#) | [Charts](#) | [Contact Imperial](#) | [About Imperial](#)
[Conditions of Use](#) | [Warranty](#) | [Opt Out](#) | [Career Opportunities](#) | [Request Info](#) | [Downloads](#) | [Privacy Policy](#) | [Links](#) | [Site Map](#) | [HELP!](#)



© 2008 Imperial Supplies LLC Questions or comments? Contact us.