

SAFETY DATA SHEET

Creation Date 27-April-2009 Revision Date 13-October-2023 Revision Number 10

1. Identification

Product Name Methanol

Cat No.: A412-1; A412-4; A412-4LC; A412-20; A412-200; A412200-001;

A412-200LC; A412-500; A412CU-1300; A412P-4; A412SK-4;

A412FB-19; A412FB-50; A412FB-115; A412FB-200; A412POP-19; A412POPB-200; A412RB50; A412RB-115; A412RB-200; A412RS-19; A412RS-28; A412RS-50; A412RS-115; A412RS-200; A412SS-115; A412SS-19; XXA412ETU200LI; NC1282211; XXA412ETWD200LI; NC1380933; A412RS-1350ASME; NC1561769; A412RS200ASME; NC1568698; NC1822351; XXA412ETU20LI; A412ETRS1350ASM; NC1871449; A412RS1350; NC1882599; XXA412ET200LI; NC1911795;

A412RS1250; NC2012101; NC2047038; NC2165479; NC2312993

CAS-No 67-56-1 Synonyms Methyl alcohol

Recommended Use Laboratory chemicals.

Uses advised against

Details of the supplier of the safety data sheet

Company

Importer/Distributor Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Manufacturer

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity

Category 3

Category 3

Category 3

Category 3

Specific target organ toxicity (single exposure)

Category 1 Target Organs - Optic nerve, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure)

Target Organs - Kidney, Liver, spleen, Blood.

Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

Toxic if swallowed, in contact with skin or if inhaled

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use non-sparking tools

Take action to prevent static discharges

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER/ doctor

Rinse mouth

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Take off contaminated clothing and wash it before reuse

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Poison, may be fatal or cause blindness if swallowed

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methanol	67-56-1	>95

4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms/effects Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 9.7 °C / 49.5 °F

Method - CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC, A.9

Autoignition Temperature 455 °C / 851 °F

Explosion Limits

 Upper
 31.00 vol %

 Lower
 6.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Formaldehyde.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards230N/A

6. Accidental release measures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use

Revision Date 13-October-2023

Methanol

personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Should not be released into the environment. See Section 12 for additional Ecological

Information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do

not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Storage. Keep container tightly closed in a dry and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases.

Metals. Peroxides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
		Columbia					
Methanol	TWA: 200 ppm	(Vacated) TWA:	IDLH: 6000 ppm				
	TWA: 262	STEL: 250 ppm	STEL: 250 ppm	TWA: 262	STEL: 250 ppm	200 ppm	TWA: 200 ppm
	mg/m³	Skin	Skin	mg/m³	Skin	(Vacated) TWA:	TWA: 260
	STEL: 250 ppm			STEL: 250 ppm		260 mg/m ³	mg/m³
	STEL: 328			STEL: 328		(Vacated) STEL:	STEL: 250 ppm
	mg/m³			mg/m³		250 ppm	STEL: 325
	Skin			Skin		(Vacated) STEL:	mg/m³
						325 mg/m ³	
						Skin	
						TWA: 200 ppm	
						TWA: 260	
						ma/m³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that evewash stations and safety showers

are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control

hazardous materials at source

Personal protective equipment

Eye Protection Tight sealing safety goggles

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	As tested under EN374-3
Viton (R)	> 480 minutes	0.70 mm	Determination of Resistance to

Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties

Physical State Liquid Colorless **Appearance** Odor Alcohol-like

No information available **Odor Threshold**

Not applicable

-98 °C / -144.4 °F **Melting Point/Range**

64.7 °C / 148.5 °F @ 760 mmHg **Boiling Point/Range**

Flash Point 9.7 °C / 49.5 °F

Method -CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC,

A.9

Evaporation Rate 5.2 (ether = 1)Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper 31.00 vol % Lower 6.0 vol % **Vapor Pressure** 128 hPa @ 20 °C

Vapor Density 1.11

Specific Gravity 0.791Miscible with water Solubility

Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 455 °C / 851 °F **Decomposition Temperature** No information available

Viscosity 0.55 cP at 20 °C Molecular Formula C H4 O **Molecular Weight** 32.04 VOC Content(%) 100

Surface tension 0.02255 N/m @ 20°C

10. Stability and reactivity

None known, based on information available **Reactive Hazard**

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Revision Date 13-October-2023

Methanol

Incompatible Materials

Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases,

Metals, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde

Hazardous polymerization does not occur. **Hazardous Polymerization**

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h	

Toxicologically Synergistic

Carbon tetrachloride

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation May cause skin and eye irritation

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Methanol	67-56-1	Not listed				

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

Teratogenicity No information available.

STOT - single exposure Optic nerve Central nervous system (CNS)

STOT - repeated exposure Kidney Liver spleen Blood

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and May cause blindness: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methanol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
		_	EC50 = 43000 mg/L 5 min	

Persistence and Degradability Persistence is unlikely based on information available.

No information available. **Bioaccumulation/ Accumulation**

Revision Date 13-October-2023

Methanol

Mobility

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methanol	-0.74

13. Disposal considerations

Waste Disposal Methods

Should not be released into the environment.

Component	RCRA -	· U Series Wastes	RCRA - P Series Wastes
Methanol - 67-56-1		U154	=

14. Transport information

DOT

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Packing Group ||

TDG

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IATA

UN-No UN1230
Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IMDG/IMO

UN-No UN1230 Proper Shipping Name METHANOL

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Methanol	67-56-1	X	-	Х	ACTIVE	200-659-6		-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Methanol	67-56-1	X	KE-23193	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Methanol	Part 1, Group A Substance		
	Part 5, Individual Substances Part 4		
	Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	,
Methanol	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methanol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methanol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 27-April-2009

 Revision Date
 13-October-2023

 Print Date
 13-October-2023

Revision Summary

This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS